

### SPECIFICATIONS

28 ft. wide, 14 ft. high, 300 sq. ft. - consult factory for larger sizes **MAXIMUM SIZE** 

**CURTAIN** Model AC - interlocking horizontal aluminum panels with clear polycarbonate glazing inserts, framed to prevent abrasion

Model AS - interlocking horizontal solid aluminum panels

**BOTTOM BAR** Rectangular aluminum extrusion

Extruded aluminum channel guides with polyester pile wear strips bolted to steel wall angles or tube supports, field adjustable **GUIDES** 

lock bar and curtain stop heights

**BARREL** 6 5/8" min, steel pipe and solid steel shaft with sealed bearing and torsion spring(s) designed for 10,000 operating cycles

**BRACKETS** 3/16" min. steel plates with sealed bearing on operator side and external tension adjustment wheel

HOOD NOT STANDARD (available as an option)

**OPERATION** Push-up to 14 ft. wide, 10 ft. high 120 sq. ft. maximum; chain, crank or motor operation on larger sizes

**LOCKS** Single cylinder or guarded thumb-turn on coil side and opposite coil side of bottom bar to activate double throw-bolt lock

Clear anodized aluminum curtain, bottom bar and guide **FINISH** 


channels, shop painted black primer on steel wall angles and brackets

WARRANTY One year limited warranty (excluding finish)


## COMMON OPTIONS



Bottom Bar With **Bottom Plate** 




### MALL PACKAGE



- 1. Motor operator with lock sensor
- 2. Emergency egress handle
- 3. Two flush mounted keystations
- 4. Steel tube supports

## **CURTAIN & BOTTOM BAR DETAILS**







MODEL AC - Clear Panel

**GUIDE DETAILS** 






Between Jamb Guide

Tube Mount Guide\*

CLEARANCES (typical face mount AC closure shown - other models simular)



- 'V' for grilles to 10 ft. high is 15"
- 'V' for grilles over 10 ft. is 17"

NOTE: 7" minimum side clearance required over 20 ft. wide or 10 ft. high with tube mount guides

### OTHER OPTIONS

- Sloping or irregular shaped bottom bars
- · Clear or bronze anodized finish
- Powder coat finish

# **GENERAL NOTES:**

Clearances are based upon standard construction. Reduced clearances and larger sizes may be available. Some options may require additional clearance. Shop drawings for specific applications are available. Consult factory for any information not shown.

\* Available as an option



4525 Littlejohn Street • Baldwin Park, CA 91706 (626) 869-0837 • Toll Free (866) 939-3399 • Fax (626) 869-0841

www.lawrencedoors.com

A-8/19