

Northwest Door® – Flush Panel Wood Sectional Door

Flush panel wood sectional doors are completely flush and have no horizontal ribs on the door face for a total sleek and uniform look. These commercial/industrial doors are available in most any size you desire including odd widths and heights. Northwest commercial wood doors are built with pride and integrity by seasoned craftsmen and have earned a reputation for maintaining the highest standards of quality.

CONSTRUCTION: Door frames are constructed using 1-1/2" thick finger-jointed West Coast kiln dried Hem/Fir stiles and rails with Tongue & Groove weather joints at meeting rails. 1/4" Luan Mahogany Plywood is attached to exterior side of the door frame (Model 071) or 1/4" Rough Sawn Plywood on the exterior (Model 076). A 1-1/2" thick polystyrene core and 1/4" Luan Mahogany Plywood back can be added to these models to increase to insulating qualities and add additional strength to the door. These models are (Model 161) with Luan Mahogany Plywood on exterior, (Model 166) with Rough Sawn Fir Plywood on exterior, and (Model 166) with 3/8" M.D.O. (Medium Density Overlay) Plywood on exterior.

NOMINAL SPECIFICATIONS:

- Frame thickness: 1-1/2"
- Top & Bottom Rail widths: 4-3/4"
- Meeting Rail Width combined: 4-1/4"
- End Stile width: 5-1/2"
- Center Stile width: 2-1/2"
- Models 161 and 166, calculated insulation rating through section, R Value 8.97
- 1 Year Limited Warranty



STANDARD WIDTHS:	8'-0"	9'-0"	10'-0"	12'-0"	16'-0"	18'-0"	20'-0"	24'-0"
Panels Horizontally	2	2	3	3	4	5	6	7

STANDARD HEIGHTS:	7'-0"	8'-0"	9'-0"	10'-0"	12'-0"	14'-0"	16'-0"
Recessed Panels Vertically	4	5	5	5	6	7	8

OPTIONS:

- Widths up to 24', heights up to 16', in one inch increments
- Wide Bottom Rails or Sloped Trailer Sections are available for sloped floors
- 1/8" clear annealed glass standard, clear obscure and insulated glass optional.
- Polyurethane insulation in lieu of Polystyrene
- Low clearance, high lift or vertical lift track and hardware also available

HARDWARE: 15" radius torsion hardware; track is 2" hemmed and bracket mounted. 3" track supplied when required by weight. Heavy duty steel rollers, non corrosive door fixtures and 14 gauge graduated hinges are standard. Double end hinges and long stem rollers are included on doors 16'-2" wide or as required by weight. U-shaped galvanized struts are supplied on doors over 14'-2" wide or as required by weight to keep the door rigid. All doors are standard with interior slide bolt lock.

Distributed By:



4525 Littlejohn St. • Baldwin Park, CA 91706
 (626) 869-0837 • (866) 939-3399 • Fax (626) 869-0841
www.lawrencedoors.com