

Northwest Door® – Raised Panel Wood Sectional Door

Raised panel wood sectional doors can add a stylish and warm appearance to commercial/industrial buildings. With a true stile and rail construction they are very versatile and can be configured to meet your needs. These panel doors are available in most any size you desire including odd widths and heights. Northwest commercial wood doors are built with pride and integrity by seasoned craftsmen, and have earned a reputation for maintaining the highest of quality standards.

CONSTRUCTION: Door frames are constructed using 1-3/4" thick finger-jointed West Coast Hem/Fir with Mortise and Tenon stiles and rails. Choose from these recessed 1/4" panel materials, Luan Mahogany Plywood Panels (Model 721), Rough Sawn Fir Plywood (Model 726), and Tempered One Side Hardboard Panels (Model 722). Raised panels are 3/4" thick, Hem/Fir Panels (Model 723), MDF Panels (Model 727), Cedar Panels (Model 728), and Redwood Panels (Model 724).

NOMINAL SPECIFICATIONS:

- Frame thickness: 1-3/4"
- Top & Bottom Rail widths: 4-7/8",
- Meeting Rail Width combined: 4-1/4"
- End Stile width: 4-7/8"
- Center Stile width: 2-5/8"
- Raised Panel thickness: 1/4" or 3/4" depending on panel material
- Finish: Face sanded ready for finish
- 1 Year Limited Warranty



STANDARD WIDTHS:	8'-0"	9'-0"	10'-0"	12'-0"	16'-0"	18'-0"	20'-0"	24'-0"
Panels Horizontally	2	2	3	3	4	5	6	7

STANDARD HEIGHTS:	7'-0"	8'-0"	9'-0"	10'-0"	12'-0"	14'-0"	16'-0"
Recessed Panels Vertically	4	5	5	5	6	7	8
Raised Panels Vertically	5	6	7	8	9	11	12

OPTIONS:

- Widths up to 24', heights up to 16', in one inch increments
- Mahogany and other select woods are available (special order)
- Flush Back of bottom section with 1/4" Luan Plywood (increases rigidity of door)
- Flush Back of door 1/4" Luan Plywood & Insulate with 5/8" Polystyrene Insulation
- Laminated Panels, 1/8" Plywood is pressure laminated to the back to help avoid splitting
- Designs, see "Design Page" this section
- Clear and clear obscure glass.
- Low clearance, high lift and vertical lift track and hardware

HARDWARE: 15" radius torsion hardware; track is 2" hemmed and bracket mounted. 3" track supplied when required by weight. Heavy duty steel rollers, non corrosive door fixtures and 14 gauge graduated hinges are standard. Double end hinges and long stem rollers are included on doors 16'-2" wide or as required by weight. U-shaped galvanized struts are supplied on doors over 14'-2" wide or as required by weight to keep the door rigid. All doors are standard with interior slide bolt lock.

Distributed By:



4525 Littlejohn St. • Baldwin Park, CA 91706
 (626) 869-0837 • (866) 939-3399 • Fax (626) 869-0841
www.lawrencedoors.com