



EG Series Folding Gates
STANDARD CONSTRUCTION

MAXIMUM SIZE	16 ft. wide (single gate) or 32 ft. wide (bi-parting gate), 12 ft. high
GATE BODY	Alternating vertical 1" x 1/2" x 11 gauge steel channels and intermediate 3/4" x 3/16" steel flat bars, spaced approximately 5" apart, with 3 rows of 3/4" x 3/16" steel lattice bars riveted together through zinc plated steel washers and traveling on formed steel clips
LEAD & REAR BARS	1 7/8" x 1 3/8" x 14 gauge formed steel box channel
LOCKING	Hasp suitable for padlocking gate in closed position (full height lock post on single gate), pivoting steel tie-back arm to hold gate in open position
BOTTOM ROLLERS	Machined steel ball bearing double-wheel non-swivel rollers traveling in 1 7/8" x 1 3/8" - 14 gauge formed steel box channel bottom track with rubber floor pads, track hinged when necessary to fold up and provide unobstructed access
TOP GUIDE	Full height vertical 1" x 1/2" x 11 gauge steel channels traveling through 1 7/8" x 2 3/8" x 14 gauge formed steel box channel top track
FINISH	Factory applied black, bronze or gray paint
WARRANTY	One year limited warranty (excluding finish)
COMMON OPTIONS	Pivoting gates Unequal pair bi-parting gates Floating gate sections Top roller with bottom guide Top roller only Quick release device Keyed pin type or cylinder locking device Gate cabinets - surface mount or recessed, shallow or deep designs Powder coat finish