



Lawrence “Auto-Reset” fire door motor operators provide time-delayed automatic closing upon activation by alarm or fail safe closing upon a loss of power. They are automatically reset when the alarm is cleared and power is restored. Selectable functions allow doors to reverse upon contact with an obstruction during automatic closing, reopen, and close again* and to automatically re-open after reset. FS operators feature an internal release device and speed governor system to control fail safe automatic closing to a typical average speed of 9” to 12” per second. Their compact “low profile” design means that no additional clearance above the top of the door coil is normally required. High-efficiency inline gear reducers provide capacities generally exceeding those of right-angle gear reduced operators with the same horsepower ratings.

An optional **R-BBU Battery Backup** system is available to prevent door closing during a loss of power for up to 7 hours[#], and support detectors and warning devices connected to it.

Standard Features


- c-UL-us Listed (UL325-2010 Compliant)
- High efficiency in-line gear reducer
- Low profile design with horizontal front of coil mounting
- Solid-state control board
- On-board open-close-stop buttons
- On-board non-resettable cycle counter
- On-board reclose timer option
- Provisions for connection of monitored & non-monitored sensing devices (multiple monitored sensing devices optional)
- Selectable constant or momentary pressure open & close
- External radio control receiver connections
- 24 volt control circuit
- Overload protection
- Adjustable linear driven limit switches
- 3-button open-close-stop wall mount control station
- NEMA 1 enclosures (NEMA 4 and 4X modifications optional)

Model FS – “Auto-Reset” Fire Door Motor Operator

- For fire doors and counter fire doors in standard cycle usage applications (up to 20,000 cycles)
- Alarm activated motor controlled closing when power is present
- Fail safe activation of internal release and governor controlled closing upon power loss
- Provision for connection of fusible link (when required by AHJ)
- Selectable time delayed closing functions
- Selectable obstruction sensing, cycling and reversing functions*
- Selectable automatic re-open function after alarm is cleared and power is restored
- Average operating speed of 6” to 8” per second
- TENV motor
- Solenoid actuated disc brake
- Delay on reverse function (*requires door be provided with a monitored sensing device*)
- 1/3, 1/2, 3/4, and 1 1/2 HP – 115v-1ph, 230v-1ph, 208/230v-3ph, 460v-3ph, 575v-3ph
- *NOTE: Consult factory for availability of larger HP, other voltages and 50Hz operators*
- Optional environmental modifications for NEMA 4 (water, oil and dust tight) and NEMA 4X (corrosion resistant) applications



R-BBU Battery Backup



NEMA 4 Modification (NEMA 4X Similar)

NOTE: Model FS fire door motor operators do not have an auxiliary chain hoist for emergency operation – if an auxiliary chain hoist is required, a Model FGH should be considered.

* Requires power be present and the operator be connected to a monitored sensing edge on the bottom of the door.

[#] R-BBU is available on 1/3 and 1/2 HP operators and can be provided with an extended battery pack to increase backup time to a total of up to 21 hours.

Lawrence FS fire door motor operators are also available as UL Classified and FM Approved Retrofit Fire Door Operators to provide the same state-of-the art technology and superior closing control for most other brands of rolling fire doors.



4525 Littlejohn Street • Baldwin Park, CA 91706
 (626) 869-0837 • Toll Free (866) 939-3399 • Fax (626) 869-0841
 www.lawrencedoors.com