



MADE IN THE USA SINCE 1925



SPECIFICATIONS

MAXIMUM SIZE

30 ft. wide, 14 ft. high, 300 sq. ft.

SL-9 straight link pattern with 5/16" horizontal aluminum rods on 2" centers, vertical chains formed from alternating single 1/8" **CURTAIN**

and double 1/16" aluminum 3-hole links on 9" centers, aluminum spacer tubes on every 10th rod, retaining rings on ends of rods

BOTTOM BAR Rectangular aluminum extrusion, self-leveling up to 1/2"

GUIDES Extruded aluminum channel guides with polyester pile wear strips and 3/16" min. steel wall angles bolted together and to the

wall with 3/8" min. fasteners 24" apart, field adjustibale lock bar and curtain stop heights

BARREL 6 5/8" steel pipe and solid steel shaft with sealed bearing and torsion spring(s) designed for 10,000 operating cycles

BRACKETS 3/16" min. steel plates with sealed bearing on operator side and external tension adjustment wheel

HOOD 24 gauge galvanized steel (NOT STANDARD - available as an option)

OPERATION Push-up to 14 ft. wide, 10 ft. high, 120 sq. ft. or chain hoist with cast iron reduction gears available on larger sizes LOCKS Single cylinder or guarded thumb-turn on coil side and opposite coil side of bottom bar to activate double throw-bolt lock **FINISH** Mill finish aluminum curtain, clear anodized aluminum bottom bar and guide channels, shop painted black primer on steel wall

angles and brackets

WARRANTY One year limited warranty (excluding finish)


COMMON OPTIONS



Bottom Bar With 4" Bottom Plate



MALL PACKAGE




- 1. Motor operator with internal lock sensor
- 2. Emergency egress release handle
- 3. Steel tube supports
- 4. Two flush mounted keystations

OTHER OPTIONS

- · Sloping or irregular shaped bottom bars
- · Clear bronze or other anodized finishes
- Powder coat finish (bottom bar, guides & hood)

CURTAIN & BOTTOM BAR DETAILS



SL9 Straight Link Curtain



Aluminum Bottom Bar


GUIDE DETAILS



Type 'Z' Guide




Type 'E' Guide





Between Jamb Guide

MOTOR OPERATOR

MODEL: SGFM







MODEL: SGFP Clearances shown are for grilles to 26 ft. wide. Consult factory for clearances on larger grilles

PS [#]	CS	AS [#]	MS#	TS#
6"	8"	6"	6"	6"

[#] Add 1/2" for tube mount grilles over 20 ft. wide or over 11 ft. high

- 'V' for grilles to 6 ft. high is 15"
- 'V' for grilles over 6 ft. to 11 ft. high is 17"
- 'V' for grilles over 11 ft. high is 19"

GENERAL NOTES:

Clearances are based upon standard door construction. Reduced clearances may be available. Some options may require additional clearance. Drive side shaft may need to be field cut to fit in clearances shown. Shop drawings for specific applications are available. Consult factory for any information not shown.





4525 Littleiohn Street • Baldwin Park, CA 91706 (626) 869-0837 • Toll Free (866) 939-3399 • Fax (626) 869-0841 www.lawrencedoors.com