



Elegant security is what the SG Grille provides. This aesthetically pleasing model offers both security and durability to keep your building or storefront safe.

FEATURES INCLUDE:

- Approximate open area of 83% for maximum airflow
- Lawrence straight link SL-9
 curtain pattern
- Up to 20,000 operating cycles
- Lever activated double throw-bolt with mortise thumb turn or cylinder lock standard
- Up to 30' wide and 14' high

COMMON APPLICATIONS:

- Retail/Mall Storefronts
- Pharmacies
- Hospitals
- Schools/Universities







Model **SG**

SPECIFICATIONS

MAXIMUM SIZE CURTAIN	30 ft. wide, 14 ft. high, 300 sq. ft. SL-9 straight link pattern with 5/16" horizontal aluminum rods on 2" centers, vertical chains formed from alternating single 1/8"
	and double 1/16" aluminum 3-hole links on 9" centers, aluminum spacer tubes on every 10th rod, retaining rings on ends of rods
BOTTOM BAR	Rectangular aluminum extrusion, self-leveling up to 1/2"
GUIDES	Extruded aluminum channel guides with polyester pile wear strips and 3/16" min. steel wall angles bolted together and to the
	wall with 3/8" min. fasteners 24" apart, field adjustibale lock bar and curtain stop heights
BARREL	6 5/8" steel pipe and solid steel shaft with sealed bearing and torsion spring(s) designed for 10,000 operating cycles
BRACKETS	3/16" min. steel plates with sealed bearing on operator side and external tension adjustment wheel
HOOD	24 gauge galvanized steel (NOT STANDARD - available as an option)
OPERATION	Push-up to 14 ft. wide, 10 ft. high, 120 sq. ft. or chain hoist with cast iron reduction gears available on larger sizes
LOCKS	Single cylinder or guarded thumb-turn on coil side and opposite coil side of bottom bar to activate double throw-bolt lock
FINISH	Mill finish aluminum curtain, clear anodized aluminum bottom bar and guide channels, shop painted black primer on steel wall
	angles and brackets
WARRANTY	One year limited warranty (excluding finish)

